



The **ZP6** is a 6 zone, two-position forced air zone control panel that can be expanded to 12 zones. The panel can be used with single-stage, multi-stage, heat pump and dual fuel equipment with up to 3 stages of heating and 2 stages of cooling. Slide switch configuration makes setup quick and easy. A wide range of control options provide ultimate application flexibility including adjustable high/low limits, adjustable high/low balance points, upstage timing, capacity control and priority cooling control.

Also available as kit including:

- ✓ Zone Panel
- ✓ Duct Temperature Sensor
- ✓ 75VA Transformer

3-Zone Expansion Panel

The **ZP6-EP** is 3-zone expansion panel is used with the ZP6 zone panel to increase the number of zones to 9 or 12.

SPECIFICATIONS:

Warranty	10 years
Construction	Aluminum enclosure with snap-on panel cover
Dimensions	13.50" H x 11.00" W x 2.00" D
Adjustable Discharge Air Limits	Low Limit is 40° F to 58° F. High Limit is 100° F to 175° F
Outdoor Balance Points	Low Balance Point (0° F to 50° F) High Balance Point (55° F to 70° F)
Purge Cycle	Off or 1 minute
Fan Mode	All zones or by zone thermostat

FEATURES AND BENEFITS:

- 6 zones expandable up to 12
- Auto changeover
- Cooling priority or majority wins
- Twenty minute time share option
- LED status indication
- Adjustable high and low limits
- Adjustable high and low balance points (requires ZPA-OTS)
- Staging by zone thermostat or built-in adjustable upstage timer
- 2nd stage capacity control option
- Purge cycle option
- Works with 2 or 3 wire zone dampers



5351 East Thompson Road Suite 142
 Indianapolis, IN 46237
 P: 888.359.0362
 F: 317.489.5204

info@iOhvaccontrols.com
 www.iOhvaccontrols.com

BOARD DIAGRAM

